



Note

**TOLERANCES:**  
Fractional  $\pm 1/4"$   
.XX =  $\pm .06$   
ANG. =  $\pm 3^\circ$   
UNLESS OTHERWISE SPECIFIED

Part Weight		Installation Torque	120 in lbs
Min/Max Temp.	-30/140 Degrees F	Conforms To ASTM	D5926, C1173
Pressure Tested		Clamps used	300 Series Stainless
Material	Flexible PVC 60 Duro Shore A	Box Quantity	

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	Reducer Bushing	Custom welded LDCR	1
2	1001-1818	Welded Coupling	1

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
FERNCO, INC. ANY REPRODUCTION IN  
PART OR AS A WHOLE WITHOUT THE  
WRITTEN PERMISSION OF FERNCO, INC.  
IS PROHIBITED.

UNITS:	INCHES	SIZE:	<b>A</b>	DESIGNER:	N. Goddard	SCALE:	not to scale
3RD ANGLE PROJECTION		CHECKER:		DATE:	1/8/2016	SHEET 1 OF 1	
DO NOT SCALE DRAWING							