



QwikSeal[®]

If you can core through it, QwikSeal can connect to it.



BENEFITS

Meets ASTM Standard

Complies with ASTM C 923 standard, ensuring quality performance.

Water-Tight Compression Seal

Ensures a water-tight compression seal up to 10 PSI and handles up to 7° of deflection in concrete manholes.

Color-Coded Identification

Features easy-to-identify colors - Grey for Sch. 40 pipe lateral and Green for SDR-35 & 26 pipe inlets - streamlining installation and reducing errors.

Universal Compatibility

QwikSeal's 5-product lineup is compatible with virtually any mainline pipe material minimizing inventory and simplifying selection.

Hassle-Free Installation

Installs easily without disturbing bedding, requiring no glues, epoxies, grouts, or difficult to use hubs.

Made in the USA

QwikSeal lateral connectors are proudly made in the United States.

FERNCO QWIKSEAL

| PART NUMBER | PIPE INLET | HOST PIPE SIZE APPLICATION |
|-------------|----------------|---|
| QS-4 | 4" SDR | 8" diameter or larger, concrete, clay or solidwall plastic pipe or 8" - 24" corrugated plastic pipe |
| QS-4S40 | 4" SCH-40 | 8" diameter or larger, concrete, clay or solidwall plastic pipe or 8" - 24" corrugated plastic pipe |
| QS-6 | 6" SDR-35 & 26 | 10" diameter or larger, concrete, clay or solidwall plastic pipe or 10" - 24" corrugated plastic pipe |
| QS-6S40 | 6" SCH-40 | 10" diameter or larger, concrete, clay or solidwall plastic pipe or 10" - 24" corrugated plastic pipe |
| QS-8 | 8" SDR-35 & 26 | 15" diameter or larger, concrete, clay or solidwall plastic pipe or 15" - 24" corrugated plastic pipe |



CORRUGATED



PVC



CLAY



CONCRETE



FERNCO HOLE SAWS FOR PLASTIC PIPE

| PART NUMBER | DESCRIPTION |
|-------------|-------------------------------------|
| QS-5x4HS | 5" OD x 4" Deep Hole Saw with Arbor |
| QS-7x4HS | 7" OD x 4" Deep Hole Saw with Arbor |
| QS-9x4HS | 9" OD x 4" Deep Hole Saw with Arbor |



- Economical, lighter and easier to handle
- General purpose tempered steel hole saw specifically designed for coring plastic pipe, even high profile corrugated
- Use with low speed - high torque hand drills

FERNCO CORING BITS FOR CONCRETE OR CLAY PIPES

| PART NUMBER | DESCRIPTION |
|-------------|--|
| QS-5x14CB | 5" OD x 14" Length Abrasive Coring Bit |
| QS-7x14CB | 7" OD x 14" Length Abrasive Coring Bit |
| QS-9x14CB | 9" OD x 14" Length Abrasive Coring Bit |



- Diamond tipped abrasive bit used for coring reinforced and non-reinforced concrete and clay pipe materials
- Use with water as coolant
- Use with all standard coring machines

Scan Here to
Learn More

